



JUBIAO CHINA

New Product Series



JB550H-1



JB550H-2



JB550H-D



JB550H-3



JB550H-4

型号 (MODEL)									
	Power	Voltage/Frequency	Cylinder	Speed	Capacity	Pressure	Tank	Weight	Overall Dimension
	kW/HP	V/Hz	mm	r/min	L/min/C.F.M	MPa/Psi	L	kg	LxWxH(cm)
JB550H-1	0.55/0.75	220/50	63.7x2	1440	110/3.9	0.7/100	10	17.5	47x22x57
JB550H-2	0.55/0.75	220/50	(63.7x2)x2	1440	220/7.8	0.7/100	25	33	80x28x55
JB550H-D	0.55/0.75	220/50	63.7x2	1440	110/3.9	0.7/100	16	40	44x37x70
JB550H-3	0.55/0.75	220/50	(63.7x2)x3	1440	330/11.7	0.7/100	70	66	100x43x70
JB550H-4	0.55/0.75	220/50	(63.7x2)x4	1440	440/15.6	0.7/100	120	85	120x49x82



JUBIAO CHINA

Direct Driven Series



LB08



LB10



ZBM25



ZBM50



ZYBFL25



ZYBFL40

型号 (MODEL)									
	Power kW/HP	Voltage/Frequency V/Hz	Cylinder mm	Speed r/min	Capacity L/min/C.F.M	Pressure MPa/Psi	Tank L	Weight kg	Overall Dimension LxWxH(cm)
LB08	0.75/1.0	220/50	Ø42x1	2800	120/4.2	0.8/115	8	14.5	49x20x48
LB10	0.75/1.0	220/50	Ø42x1	2800	120/4.2	0.8/115	10	16.5	49x20x48
ZBM25	1.1/1.5	220/50	Ø42x1	2800	160/5.6	0.8/115	25	20	56x25x61
ZBM50	1.1/1.5	220/50	Ø42x1	2800	160/5.6	0.8/115	50	28.5	66x30x65
ZYBFL25	1.5/2.0	220/50	Ø47x1	2800	192/6.7	0.8/115	25	24	61x26x58
ZYBFL40	1.5/2.0	220/50	Ø47x1	2800	192/6.7	0.8/115	40	30	67x30x61



ISO9001

SGS



Direct Driven Series



ZBM25A



ZBM50A



CEBM25



CEBM50



ZFL25



ZFL50

型号 (MODEL)									
	Power kW/HP	Voltage/Frequency V/Hz	Cylinder mm	Speed r/min	Capacity L/min/C.F.M	Pressure MPa/Psi	Tank L	Weight kg	Overall Dimension LxWxH(cm)
ZBM25A	1.5/2.0	220/50	47x1	2800	192/6.7	0.8/115	25	21.5	59x26x61.5
ZBM50A	1.5/2.0	220/50	47x1	2800	192/6.7	0.8/115	50	26.5	67x32x66
CEBM25	1.8/2.5	220/50	47x1	2800	233/8.2	0.8/115	25	22.5	59x25x61.5
CEBM50	1.8/2.5	220/50	47x1	2800	233/8.2	0.8/115	50	29.5	67x32x67
ZFL25	1.5/2.0	220/50	47x1	2800	160/5.6	0.8/115	25	22.5	56x26x57
ZFL50	1.5/2.0	220/50	47x1	2800	192/6.6	0.8/115	50	33.5	71x33x65



JUBIAO CHINA

Direct Driven Series



ZFL25A



ZFL50A



CEFL25



CEFL50



ZMC50



ZVA50

型号 (MODEL)									
	Power kW/HP	Voltage/Frequency V/Hz	Cylinder mm	Speed r/min	Capacity L/min/C.F.M	Pressure MPa/Psi	Tank L	Weight kg	Overall Dimension LxWxH(cm)
ZFL25A	1.5/2.0	220/50	47x1	2800	192/6.7	0.8/115	25	23.5	56x27x57.5
ZFL50A	1.5/2.0	220/50	47x1	2800	192/6.7	0.8/115	50	33.5	71x33x65
CEFL25	1.8/2.5	220/50	47x1	2800	233/8.2	0.8/115	25	24	56x27x58
CEFL50	1.8/2.5	220/50	47x1	2800	233/8.2	0.8/115	50	35	74x33x66
ZMC50	2.2/3.0	220/50	48x1	2800	192/6.7	0.8/115	50	30	70x33x66
ZVA50	2.2/3.0	220/50	47x2	2800	250/8.8	0.8/115	50	50	73x34x67



ISO9001

SGS



Gas Online Engine Series



JBG-1.1/5



JBG-0.25/8

Belt Driven Series



Z-0.036/8



V-0.12/8

型号 (MODEL)									
	Power kW/HP	Voltage/Frequency V/Hz	Cylinder mm	Speed r/min	Capacity L/min/C.F.M	Pressure MPa/Psi	Tank L	Weight kg	Overall Dimension LxWxH(cm)
JBG-1.1/5	11/15		95x3	1050	1100/38.8	0.5/72.5	70	70	143x88x105
JBG-0.25/8	4.0/5.5		65x2	980	250/8.8	0.8/115	100	87	117x45x87
Z-0.036/8	0.75/1.0	220/50	51x1	950	36/1.27	0.8/115	30	47	77x39x66
V-0.12/8	1.1/1.5	220/50	51x2	1020	120/4.2	0.8/115	40	50	86x45x73



JUBIAO CHINA

Belt Driven Series



V-0.17/8



V-0.25/8

Belt Driven Series



W-0.36/8



V-0.48/8
V-0.6/8

型号 (MODEL)									
	Power	Voltage/Frequency	Cylinder	Speed	Capacity	Pressure	Tank	Weight	Overall Dimension
	kW/HP	V/Hz	mm	r/min	L/min/C.F.M	MPa/Psi	L	kg	LxWxH(cm)
V-0.17/8	1.5/2.0	220/50	51X2	1120	170/6.0	0.8/115	50	58	103x46x77
V-0.25/8	2.2/3.0	220/50	65X2	1080	250/8.8	0.8/115	60	75	110x45x82
W-0.36/8	3.0/4.0	380/50	65X3	1080	360/12.7	0.8/115	90	92	125x49x89
V-0.48/8	4.0/5.5	380/50	80X2	1000	480/16.9	0.8/115	100	105	123x50x100
W-0.6/8	5.0/6.5	380/50	90X2	1020	600/21.2	0.8/115	100	115	123x50x100



Belt Driven Series

ISO9001

SGS



W-0.67/8



W-0.9/8



V-0.2/12.5



W-0.3/12.5
W-0.58/12.5
W-0.8/12.5

型号 (MODEL)									
	Power kW/HP	Voltage/Frequency V/Hz	Cylinder mm	Speed r/min	Capacity L/min/C.F.M	Pressure MPa/Psi	Tank L	Weight kg	Overall Dimension LxWxH(cm)
W-0.67/8	5.5/7.5	380/50	80x3	980	670/23.7	0.8/115	120	172	143x60x110
W-0.9/8	7.5/10	380/50	90x3	980	900/31.8	0.8/115	180	180	156x60x110
V-0.2/12.5	1.5/2.0	220/50	65x1/51x1	980	200/7.1	1.25/180	70	70	110x45x82
W-0.3/12.5	3.0/4.0	380/50	65x2/51x1	980	300/10.6	1.25/180	90	89	125x49x89
W-0.58/12.5	4.0/5.5	380/50	80x2/65x1	980	580/20.5	1.25/180	100	110	143x60x110
W-0.8/12.5	7.5/10	380/50	90x2/80x1	980	800/28.2	1.25/180	180	175	156x60x110



JUBIAO CHINA



W-1.5/8



W-2.0/8

Italy Style Compressor



JB-2055
JB-2065
JB-2070



JB-2055(50L)

型号 (MODEL)									
	Power kW/HP	Voltage/Frequency V/Hz	Cylinder mm	Speed r/min	Capacity L/min/C.F.M	Pressure MPa/Psi	Tank L	Weight kg	Overall Dimension LxWxH(cm)
W-1.5/8	11/15	380/50	100x3	980	1500/53	0.8/115	320	254	181x73x129
W-2.0/8	15/20	380/50	120x3	980	2000/70.6	0.8/115	350	330	195x74x143
JB-2055	1.5/2.0	220/50	55x2	980	120/4.2	0.8/115	100	63	122x46x63
JB-2065	1.8/2.5	220/50	65x2	980	170/6.0	0.8/115	100	64	122x46x84
JB-2070	2.2/3.0	220/50	70x2	980	250/8.8	0.8/115	100	905	122x46x85
JB-2055	1.5/2.0	220/50	55x2	980	120/4.2	0.8/115	50	61.5	80x40x72

Air Pump D-Series



DZ1051



DV2051



DV2051A



DV2065



DW3065



DV2080



DV2090



DW3080



DW3090



DW3100



DW3120



DV2105T

Air Pump O-Series



OV2060



OV2070



OW3070



OV2080



JUBIAO CHINA



3/8" 1/2"



1/2"



1/4"



1/2"



Pressure regulator assembly



3/4"



1/4"



Safety valve



T-40



T-50



T-60



Y-40



Y-50



Y-60



Connect rod



Piston



Piston pin



Piston rings



Gasket



Valve strip



Plastic handle



Overload Protector



One way
JBS-1



One way
JBS-2



One way
JBS-3



Four way
JBS-4



One way three phase
JBS-5



Electromagnetic
starter



Switch assembly
JBS-6



Switch assembly
JBS-7



JUBIAO CHINA



Non-return Valve



JBF-1



JBF-2



JBF-3



JBF-70



JBF-4



JBF-5



JBF-6



JBF-7



7" Wheel
JBP-1



JBN-2



JBF-1



JBN-1